

Interface FLOR | Heuga 726

SPECIFICATION

Product definition	Tufted Plain Level Loop Tile	Style number	6072600005
Pile Material	100% Solution Dyed Nylon	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	520g/m ² ±5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501) DIN 4102 B1 (NFP 92-506) (PV No.RA 99-219) M3
Effective pile yarn weight	350g/m ² ± 10%	Hot Metal Nut	Pass, low radius of effects of ignition
Total Weight	4200g/m ² ±5%	Castor Chair Rating	≥ 2,4 (EN 985)
Pile Height	2,6 mm ± 0,4 mm	Dimensional Stability	≤ 0.2% (ISO 2551)
Total Thickness	5,6 mm ± 0,3 mm	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Gauge/Ends per 10cm	1/10 - 41	Colour Fastness - Light	>7 (ISO 105/B02)
Tufts per m²	159,000 ± 5%	Tiles per Box	20 - 5m ² (50 x 50 cm ± 0,2%)
Backing Type	Graphlex®		

CE
06
0336-CPD-8538

EN 1307

Quarter Tuft Monolithic
20591 23 dB
NF UPEC
Environmental Product Scheme
Certificate Number ENP 342



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interfaceflor.eu